Acer Travelmate 273X

The TravelMate 270 series has been especially designed for the outbound professional user, either self-employed or working in small, medium and large corporations, looking for a powerful work tool that integrates multimedia, communication and performance features required to meet the challenges of today's business-critical applications. High-quality audio and video, real-time access to Internet and office network, simple system set-up and installation as well as hassle-free management of cables, storage devices and other accessories - these are the comprising needs of mobile professionals who need to keep up with today's fast-moving business world. The TravelMate 270, with its all-in-one design, integrates the power and the latest innovations in connectivity to ensure that executives and professionals maintain a high level of performance and productivity, even and especially when undertaking outbound work. Especially designed for demanding multimedia applications, this notebook PC is the excellent solution for graphics intensive presentations and audio-visual shows.

General	
Recommended Use	Small business, corporate business
System Type	Notebook
Built-in Devices	Microphone, stereo speakers, keyboard, touchpad, display
Width	32.2 cm
Depth	27.2 cm
Height	3.8 cm
Weight	3 kg
Localisation	German / Germany

Processor	
Processor	Intel Pentium 4-M 1.7 GHz
Data Bus Speed	400 MHz
Features	Deeper Sleep, Enhanced SpeedStep technology, streaming SIMD extensions 2, MMX instructions set
Chipset Type	SiS650

Copyright © 2006 dooyoo AG www.dooyoo.co.uk

Downloaded from www.Manualslib.com manuals search engine

Cache Memory	
Type	L2 Cache - Advanced Transfer Cache
Installed Size	512 KB

RAM	
Installed Size	256 MB / 1 GB (max)
Technology	DDR SDRAM - 266 MHz
Memory Specification Compliance	PC2100
Form Factor	SO DIMM 200-pin

Storage Controller	
Type	IDE

Storage	
Floppy Drive	3.5" 1.44 MB floppy - integrated
Hard Drive	20 GB

Optical Storage	
Type	CD-ROM - integrated
Read Speed	24x

Display	
Display Type	14.1" TFT active matrix
Max Resolution	1024 x 768 (XGA)
Widescreen Display	No
Colour support	24-bit (16.7 million colours)

Video	
Graphics Processor / Vendor	SiS 650 - AGP 4x
Video Memory	Shared Video Memory (UMA)

Audio	
Audio Output	Sound card
Compliant Standards	DirectSound, AC '97, Sound Blaster Pro
Audio Input	Microphone

Input Device(s)	
Type	Keyboard, touchpad, 4-way scroll button

Copyright © 2006 dooyoo AG www.dooyoo.co.uk

Downloaded from www.Manualslib.com manuals search engine

Telecom	
Modem	Fax / modem
Max Transfer Rate	56 Kbps
Protocols & Specifications	ITU V.90 , Hayes AT command set

Networking	
Networking	Network adapter
Data Link Protocol	Ethernet, Fast Ethernet

Expansion / Connectivity	
Expansion Slots Total (Free)	1 (1) x CardBus - type III (2 x type I / II) Â¦ 2 memory - SO DIMM 200-pin
Interfaces	1 x modem - phone line - RJ-11 Â¦ 1 x network - Ethernet 10Base-T/100Base-TX - RJ-45 Â¦ 1 x parallel - IEEE 1284 (EPP/ECP) - 25 pin D-Sub (DB-25) Â¦ 1 x serial - RS-232C - 9 pin D-Sub (DB-9) Â¦ 1 x keyboard / mouse - generic - 6 pin mini-DIN (PS/2 style) Â¦ 1 x display / video - VGA - 15 pin HD D-Sub (HD-15) Â¦ 1 x audio - line-out/headphones - mini-phone stereo 3.5 mm Â¦ 1 x audio - line-in/microphone - mini-phone 3.5mm Â¦ 3 x USB - 4 PIN USB Type A Â¦ 1 x IEEE 1394 (FireWire) Â¦ 1 x display / video - S-video output - 4 PIN mini-DIN

Miscellaneous	
Features	Security lock slot (cable lock sold separately), administr ator password, wake on LAN, Wake on Ring
Compliant Standards	ACPI 2.0

Power	
Power Device	External
Voltage Required	AC 100/240 V (50/60 Hz)
Power Provided	65 Watt

Copyright © 2006 dooyoo AG www.dooyoo.co.uk

Downloaded from www.Manualslib.com manuals search engine

Battery	
Technology	Lithium Ion
Installed Qty	1
Capacity	57 Wh
Run Time (Up To)	3 hour(s)
Recharge Time	3 hour(s)

Operating System / Software	
OS Provided	Microsoft Windows 2000 / XP Professional
Software	Drivers & Utilities, Adobe Acrobat Reader, Norton AntiVirus, Acer System Recovery, Acer Launch Manager

Manufacturer Warranty	
Service & Support	2 years warranty
Service & Support Details	Limited warranty - 2 years

Environmental Parameters	
Min Operating Temperature	5 Â°C
Max Operating Temperature	35 Â°C
Humidity Range Operating	20 - 80%

Copyright © 2006 dooyoo AG www.dooyoo.co.uk

Downloaded from www.Manualslib.com manuals search engine